AM-TANK 105+13









Portable 105+13-gallon tanks manufactured in high density linear roto-molded polyethylene for the safe and reliable transport and supply of Diesel and DEF. AM-TANK 105+13 offers a lightweight, robust, and portable tank solution giving users the ultimate convenience to refuel their fleet remotely on-site. Assembled and ready to use, this innovative tank can be easily loaded on the back of the pick-up truck and quickly plugged to the truck battery.

Tanks are equipped with:

- 2" filling plug equipped with three-effects (pressure/de-pressure/overturning) air vent device for both Diesel and DEF section.
- Integrated forklift pockets (to lift when full).
- Integrated handles (to lift when empty).
- Integrated recesses for securing with ratchet lashing straps during transport.
- Integrated covering lid to provide protection against bad weather conditions, UV rays and equipped with lockable draw latches.
- Suction net filter to stop and separate impurities (Diesel section only).
- Fuel level indicator (Diesel section only)
- DEF tank can be removed. The remaining space can be used as tool tray when DEF tank is not being utilized.

Fuel Transfer Unit DIESEL section:

- 12 GPM Diesel DC Transfer Pump (12V, 300 Watt, 22 Amp, Duty Cycle: 30 minutes on/off, 2900 RPM, ON/OFF switch, IP55 rated).
- 13 ft. Cable with clamps.
- 13 ft. of flexible dispensing hose.
- A60 Auto-nozzle.

Features:

Nominal capacity: 105+13 gal [400 + 50 lt]
Tank total length: 47,2 in [120 cm]
Tank total width: 31,5 in [80 cm]
Tank total height: 30,9 in [78,5 cm]
Tank total weight**: 121 lbs [55 kg]

**(including fuel unit and accessories)

Fuel Transfer Unit DEF section:

- 4 GPM Submersible DEF 12V DC Transfer Pump. It is powered by the same 12 volt source as the Diesel section with a separate power plug. No additional power cables are required.
- 13 ft. of flexible dispensing hose.
- Manual nozzle.