

## AM-TANK 253



Portable 253-gallon tanks manufactured in high density linear roto-molded polyethylene for the safe and reliable transport and supply of Diesel only. AM-TANK 253 offers a lightweight, robust, and portable tank solution giving users the ultimate convenience to refuel their fleet remotely on-site. Assembled and ready to use, this innovative tank can be easily loaded on the back of the pick-up truck and quickly plugged to the truck battery.

### Tanks are equipped with:

- 2" filling plug equipped with three-effects (pressure/de-pressure/overturning) air vent device.
- Its transparency also allows a constant sight monitoring of the fuel level.
- It can be easily washed with regular detergents thanks to its highly smooth surface.
- Side pockets, reinforced by zinc-coated carbon steel profiles, allow lifting with forklift (full load).
- Integrated top hooks (to lift when empty).
- Integrated and lockable covering lid to provide protection against bad weather conditions, UV rays.
- Suction net filter to stop and separate impurities.
- 220 mm diameter top hatch with lockable screw lid for maintenance and cleaning.
- Internal breakwater ball to balance the vehicle during the transport with half-full tank.

### Fuel Transfer Unit:

- 12 GPM Diesel DC Transfer Pump (12V, 300 Watt, 22 Amp, Duty Cycle: 30 minutes on/off, 2900 RPM, ON/OFF switch, IP55 rated).
- 13 ft. Cable with clamps.
- 13 ft. of flexible dispensing hose.
- A60 Auto-nozzle.

### Features:

- Nominal capacity: 253 gal [960 lt]
- Tank total length: 70,8 in [180 cm]
- Tank total width: 39,3 in [100 cm]
- Tank total height: 39,3 in [100 cm]
- Tank total weight\*\* : 249 lbs [113 kg]

\*\* (including fuel unit and accessories)

