## ded polyethylene for the safe rs a lightweight, robust, and their fleet remotely on-site. It on the back of the pick-up erturning) air vent device. Fansport. Inditions, UV rays and Max. Amp.


## **AM-TANK 58 DEF**



AM - TANK



Portable 58-gallon tanks manufactured in high density linear roto-molded polyethylene for the safe and reliable transport and supply of DEF / AdBlue. AM-TANK 58 offers a lightweight, robust, and portable tank solution giving users the ultimate convenience to refuel their fleet remotely on-site. Assembled and ready to use, this innovative tank can be easily loaded on the back of the pick-up truck and quickly plugged to the truck battery.



- 2" filling plug equipped with three-effects (pressure/de-pressure/overturning) air vent device.
- Integrated forklift pockets (to lift when full).
- Integrated handles (to lift when empty).
- Integrated recesses for securing with ratchet lashing straps during transport.
- Integrated covering lid to provide protection against bad weather conditions, UV rays and equipped with lockable draw latches.
- Suction net filter to stop and separate impurities.

## **Fuel Transfer Unit:**

- 9 GPM DEF transfer pump, 12V DC, Duty cycle: 30mins, 260W, 22 Max. Amp.
- 13 ft cable with clamps for battery connection
- 13 ft. flexible dispensing hose
- Manual nozzle.

## Features:

i catules.		
<ul> <li>Nominal capacity:</li> </ul>	58 gal	[220 lt]
<ul><li>Tank total length:</li></ul>	35,8 in	[91 cm]
<ul><li>Tank total width:</li></ul>	23,6 in	[60 cm]
<ul><li>Tank total height:</li></ul>	24,4 in	[62 cm]
<ul> <li>Tank total weight**:</li> </ul>	52 lbs	[24 kg]

<sup>\*\*(</sup>including fuel unit and accessories)