

## AM-TANK 58



Portable 58-gallon tanks manufactured in high density linear roto-molded polyethylene for the safe and reliable transport and supply of Diesel only. AM-TANK 58 offers a lightweight, robust, and portable tank solution giving users the ultimate convenience to refuel their fleet remotely on-site. Assembled and ready to use, this innovative tank can be easily loaded on the back of the pick-up truck and quickly plugged to the truck battery.

### Tanks are equipped with:

- 2" filling plug equipped with three-effects (pressure/de-pressure/overturning) air vent device.
- Integrated forklift pockets (to lift when full).
- Integrated handles (to lift when empty).
- Integrated recesses for securing with ratchet lashing straps during transport.
- Integrated covering lid to provide protection against bad weather conditions, UV rays and equipped with lockable draw latches.
- Suction net filter to stop and separate impurities.

### Fuel Transfer Unit:

- 12 GPM Diesel DC Transfer Pump (12V, 300 Watt, 22 Amp, Duty Cycle: 30 minutes on/off, 2900 RPM, ON/OFF switch, IP55 rated).
- 13 ft. Cable with clamps.
- 13 ft. of flexible dispensing hose.
- A60 Auto-nozzle.

### Features:

- Nominal capacity: 58 gal [220 lt]
- Tank total length: 35,8 in [91 cm]
- Tank total width: 23,6 in [60 cm]
- Tank total height: 24,4 in [62 cm]
- Tank total weight\*\* : 52 lbs [24 kg]

\*\* (including fuel unit and accessories)

